

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## Shell Tellus S4 VX 32

Version 2.1      Revision Date: 03/04/2021      SDS Number: 800010030788      Print Date: 03/05/2021  
Date of last issue: 08/31/2018

---

### SECTION 1. IDENTIFICATION

Product name : Shell Tellus S4 VX 32

Product code : 001G4231

#### Manufacturer or supplier's details

Manufacturer/Supplier : **Shell Oil Products US**  
PO Box 4427  
Houston TX 77210-4427  
USA

SDS Request : (+1) 877-276-7285  
Customer Service :

#### Emergency telephone number

Spill Information : 877-504-9351  
Health Information : 877-242-7400

#### Recommended use of the chemical and restrictions on use

Recommended use : Hydraulic oil

Restrictions on use :  
The Environmental Protection Agency prohibits processing and distribution of this chemical/product for any use other than in aviation hydraulic fluid in aircraft systems lubricants and greases, and new or replacement parts for automobiles and other motor vehicles. In addition, all persons are prohibited from releasing PIP (3:1) to water during manufacturing, processing, distribution in commerce, and commercial use of PIP (3:1).

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity (Inhalation) : Category 4

Skin irritation : Category 2

Reproductive toxicity : Category 2

Long-term (chronic) aquatic hazard : Category 2

#### GHS label elements

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Tellus S4 VX 32

Version  
2.1

Revision Date:  
03/04/2021

SDS Number:  
800010030788

Print Date: 03/05/2021  
Date of last issue: 08/31/2018

Hazard pictograms

:



Signal word

: Warning

Hazard statements

: **PHYSICAL HAZARDS:**  
Not classified as a physical hazard under GHS criteria.  
**HEALTH HAZARDS:**  
H332 Harmful if inhaled.  
H315 Causes skin irritation.  
H361f Suspected of damaging fertility.  
**ENVIRONMENTAL HAZARDS:**  
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**  
P201 Obtain special instructions before use.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash hands thoroughly after handling.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
**Response:**  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
**Storage:**  
No precautionary phrases.  
**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

Contains Distillates (petroleum), hydrotreated middle.

Contains Triphenyl Phosphate Isopropylated (5% Or More Tpp)

### Other hazards which do not result in classification

Used oil may contain harmful impurities.

High-pressure injection under the skin may cause serious damage including local necrosis.

Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

Chemical nature

: Blend of petroleum distillates and additives.  
Highly refined mineral oil.  
The highly refined mineral oil is only present as additive diluent.  
The highly refined mineral oil contains <3% (w/w) DMSO-

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Tellus S4 VX 32

Version  
2.1

Revision Date:  
03/04/2021

SDS Number:  
800010030788

Print Date: 03/05/2021  
Date of last issue: 08/31/2018

extract, according to IP346.  
Classification based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).

### Hazardous components

| Chemical name   | Synonyms                                     | CAS-No.    | Concentration (% w/w) |
|---|--|------------|-----------------------|
| Distillates (petroleum), hydrotreated middle                      | Distillates (petroleum), hydrotreated middle | 64742-46-7 | 60 - 80               |
| Phenol, isopropylated, phosphate (3:1) [Triphenyl phosphate > 5%] | Phenol, isopropylated, phosphate (3:1)       | 68937-41-7 | 0.1 - 0.9             |
| Butylated hydroxytoluene  | 2,6-di-tert-butyl-p-cresol                   | 128-37-0   | 0.1 - 0.5             |

### SECTION 4. FIRST-AID MEASURES

- If inhaled : Call emergency number for your location / facility.
- Remove to fresh air. Do not attempt to rescue the victim unless proper respiratory protection is worn. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting, or unresponsive, give 100% oxygen with rescue breathing or Cardio-Pulmonary Resuscitation as required and transport to the nearest medical facility.
- In case of skin contact : Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.
- When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop.  
Obtain medical attention even in the absence of apparent wounds.
- In case of eye contact : Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing.  
If persistent irritation occurs, obtain medical attention.
- If swallowed : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
- Most important symptoms and effects, both acute and delayed : Skin irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blisters.  
Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Tellus S4 VX 32

Version  
2.1

Revision Date:  
03/04/2021

SDS Number:  
800010030788

Print Date: 03/05/2021  
Date of last issue: 08/31/2018

---

Ingestion may result in nausea, vomiting and/or diarrhoea. Local necrosis is evidenced by delayed onset of pain and tissue damage a few hours following injection.

Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.

Indication of any immediate medical attention and special treatment needed : High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimise tissue damage and loss of function. Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetics, and wide exploration is essential.

---

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : Do not use water in a jet.

Specific hazards during fire-fighting : Hazardous combustion products may include:  
A complex mixture of airborne solid and liquid particulates and gases (smoke).  
Carbon monoxide may be evolved if incomplete combustion occurs.  
Unidentified organic and inorganic compounds.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Avoid contact with skin and eyes.

Environmental precautions : Local authorities should be advised if significant spillages cannot be contained.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## Shell Tellus S4 VX 32

Version  
2.1

Revision Date:  
03/04/2021

SDS Number:  
800010030788

Print Date: 03/05/2021  
Date of last issue: 08/31/2018

---

Methods and materials for containment and cleaning up : Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.

Additional advice : For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

---

### SECTION 7. HANDLING AND STORAGE

Technical measures : Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

Advice on safe handling : Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.

Avoidance of contact : Strong oxidising agents.

Product Transfer : Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.

Further information on storage stability : Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers. Must be stored in a diked (bunded) area.  
  
Store at ambient temperature.

Packaging material : Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.

Container Advice : Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Tellus S4 VX 32

Version  
2.1

Revision Date:  
03/04/2021

SDS Number:  
800010030788

Print Date: 03/05/2021  
Date of last issue: 08/31/2018

### SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### Components with workplace control parameters

| Components               | CAS-No.      | Value type (Form of exposure)      | Control parameters / Permissible concentration | Basis    |
|--------------------------|--------------|------------------------------------|--|----------|
| Oil mist, mineral        | Not Assigned | TWA (Mist)                         | 5 mg/m <sup>3</sup>                            | OSHA Z-1 |
| Oil mist, mineral        |              | TWA (Inhalable particulate matter) | 5 mg/m <sup>3</sup>                            | ACGIH    |
| Butylated hydroxytoluene | 128-37-0     | TWA (Inhalable fraction and vapor) | 2 mg/m <sup>3</sup>                            | ACGIH    |

#### Biological occupational exposure limits

No biological limit allocated.

#### Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods <http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods <http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances <http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany <http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

**Engineering measures** : The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:  
Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:  
Define procedures for safe handling and maintenance of

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Tellus S4 VX 32

Version  
2.1

Revision Date:  
03/04/2021

SDS Number:  
800010030788

Print Date: 03/05/2021  
Date of last issue: 08/31/2018

controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.

Practice good housekeeping.

### Personal protective equipment

Respiratory protection : No respiratory protection is ordinarily required under normal conditions of use.  
In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.  
If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.  
Check with respiratory protective equipment suppliers.  
Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.  
Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].

Hand protection  
Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Tellus S4 VX 32

Version  
2.1

Revision Date:  
03/04/2021

SDS Number:  
800010030788

Print Date: 03/05/2021  
Date of last issue: 08/31/2018

time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

- Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.
- Skin and body protection : Wear chemical resistant gloves/gauntlets and boots. Where risk of splashing, also wear an apron.
- Protective measures : Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.
- Thermal hazards : Not applicable

### Environmental exposure controls

- General advice : Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : colourless
- Odour : Slight hydrocarbon
- Odour Threshold : Data not available
- pH : Not applicable
- pour point : Method: Unspecified  
Not applicable
- Melting / freezing point : Data not available
- Initial boiling point and boiling range : > 280 °C / 536 °F  
estimated value(s)
- Flash point : >= 100 °C / >= 212 °F  
Method: EN ISO 2592



# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## Shell Tellus S4 VX 32

Version  
2.1

Revision Date:  
03/04/2021

SDS Number:  
800010030788

Print Date: 03/05/2021  
Date of last issue: 08/31/2018

---

|  |   |  |
|--|---|--|
| Evaporation rate                                 | : | Data not available   |
| Flammability (solid, gas)                        | : | Data not available   |
| Upper explosion limit / upper flammability limit | : | Typical 10 %(V)  |
| Lower explosion limit / Lower flammability limit | : | Typical 1 %(V)   |
| Vapour pressure                                  | : | < 0.5 Pa (20 °C / 68 °F)<br>estimated value(s)                           |
| Relative vapour density                          | : | > 1<br>estimated value(s)  |
| Relative density                                 | : | 0.866 (15 °C / 59 °F)  |
| Density  | : | 866 kg/m <sup>3</sup> (15.0 °C / 59.0 °F)<br>Method: DIN EN ISO 12185    |
| Solubility(ies)                                  |   |  |
| Water solubility                                 | : | negligible   |
| Solubility in other solvents                     | : | Data not available   |
| Partition coefficient: n-octanol/water           | : | log Pow: > 6<br>(based on information on similar products)               |
| Auto-ignition temperature                        | : | > 320 °C / 608 °F  |
| Decomposition temperature                        | : | Data not available   |
| Viscosity  |   |  |
| Viscosity, dynamic                               | : | Data not available   |
| Viscosity, kinematic                             | : | 28.8 - 35.2 mm <sup>2</sup> /s (40.0 °C / 104.0 °F)<br>Method: ASTM D445 |
| Explosive properties                             | : | Not classified   |
| Oxidizing properties                             | : | Data not available   |
| Conductivity                                     | : | This material is not expected to be a static accumulator.                |

---

### SECTION 10. STABILITY AND REACTIVITY

|            |   |  |
|------------|---|--|
| Reactivity | : | The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph. |
|------------|---|--|

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## Shell Tellus S4 VX 32

Version  
2.1

Revision Date:  
03/04/2021

SDS Number:  
800010030788

Print Date: 03/05/2021  
Date of last issue: 08/31/2018

---

|                                    |   |   |
|------------------------------------|---|---|
| Chemical stability                 | : | Stable.   |
| Possibility of hazardous reactions | : | Reacts with strong oxidising agents.                |
| Conditions to avoid                | : | Extremes of temperature and direct sunlight.        |
| Incompatible materials             | : | Strong oxidising agents.                            |
| Hazardous decomposition products   | : | No decomposition if stored and applied as directed. |

---

### SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment : Information given is based on data on the components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

#### Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

#### Acute toxicity

##### Product:

|                           |   |   |
|---------------------------|---|---|
| Acute oral toxicity       | : | LD50 (rat): > 5,000 mg/kg<br>Remarks: Low toxicity:<br>Based on available data, the classification criteria are not met.    |
| Acute inhalation toxicity | : | LC 50 (Rat): > 1 - < 5 mg/l<br>Exposure time: 4 h<br>Remarks: Harmful if inhaled.   |
| Acute dermal toxicity     | : | LD50 (Rabbit): > 5,000 mg/kg<br>Remarks: Low toxicity:<br>Based on available data, the classification criteria are not met. |

#### Skin corrosion/irritation

##### Product:

Remarks: Causes skin irritation.

#### Serious eye damage/eye irritation

##### Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

#### Respiratory or skin sensitisation

##### Product:

Remarks: Not a skin sensitiser.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## Shell Tellus S4 VX 32

Version  
2.1

Revision Date:  
03/04/2021

SDS Number:  
800010030788

Print Date: 03/05/2021  
Date of last issue: 08/31/2018

---

Based on available data, the classification criteria are not met.

### Germ cell mutagenicity

**Product:**

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

### Carcinogenicity

**Product:**

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skin-painting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### Reproductive toxicity

**Product:**

: Remarks: Suspected of damaging fertility., Not a developmental toxicant., Based on available data, the classification criteria are not met.

### STOT - single exposure

**Product:**

Remarks: Based on available data, the classification criteria are not met.

### STOT - repeated exposure

**Product:**

Remarks: Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Tellus S4 VX 32

Version  
2.1

Revision Date:  
03/04/2021

SDS Number:  
800010030788

Print Date: 03/05/2021  
Date of last issue: 08/31/2018

### Aspiration toxicity

**Product:**

Not an aspiration hazard.

### Further information

**Product:**

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

Remarks: Slightly irritating to respiratory system.

---

## SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment : Ecotoxicological data have not been determined specifically for this product.  
Information given is based on a knowledge of the components and the ecotoxicology of similar products.  
Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).

### Ecotoxicity

**Product:**

Toxicity to fish (Acute toxicity) : Remarks: LL/EL/IL50 > 1 <= 10 mg/l  
Toxic

Toxicity to daphnia and other aquatic invertebrates (Acute toxicity) : Remarks: LL/EL/IL50 > 1 <= 10 mg/l  
Toxic

Toxicity to algae (Acute toxicity) : Remarks: LL/EL/IL50 > 1 <= 10 mg/l  
Toxic

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: Data not available

Toxicity to microorganisms (Acute toxicity) : Remarks: Data not available

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## Shell Tellus S4 VX 32

Version  
2.1

Revision Date:  
03/04/2021

SDS Number:  
800010030788

Print Date: 03/05/2021  
Date of last issue: 08/31/2018

---

### Components:

#### **Phenol, isopropylated, phosphate (3:1) [Triphenyl phosphate > 5%]:**

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 10

#### **Butylated hydroxytoluene:**

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

### **Persistence and degradability**

#### Product:

Biodegradability : Remarks: Not readily biodegradable.  
Major constituents are inherently biodegradable, but contains components that may persist in the environment.

### **Bioaccumulative potential**

#### Product:

Bioaccumulation : Remarks: Contains constituents with the potential to bioaccumulate.

### **Mobility in soil**

#### Product:

Mobility : Remarks: Liquid under most environmental conditions.  
If it enters soil, it will adsorb to soil particles and will not be mobile.

Remarks: Floats on water.

### **Other adverse effects**

#### Product:

Additional ecological information : Does not have ozone depletion potential, photochemical ozone creation potential or global warming potential.  
Product is a mixture of non-volatile components, which will not be released to air in any significant quantities under normal conditions of use.

Poorly soluble mixture.  
Causes physical fouling of aquatic organisms.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Tellus S4 VX 32

Version  
2.1

Revision Date:  
03/04/2021

SDS Number:  
800010030788

Print Date: 03/05/2021  
Date of last issue: 08/31/2018

---

Mineral oil does not cause chronic toxicity to aquatic organisms at concentrations less than 1 mg/l.

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues

: Recover or recycle if possible.  
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.  
Do not dispose into the environment, in drains or in water courses

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.  
Waste, spills or used product is dangerous waste.  
Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.  
Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging

: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.  
Disposal should be in accordance with applicable regional, national, and local laws and regulations.

#### Local legislation

Remarks

: Disposal should be in accordance with applicable regional, national, and local laws and regulations.

---

### SECTION 14. TRANSPORT INFORMATION

#### National Regulations

##### US Department of Transportation Classification (49 CFR Parts 171-180)

Not regulated as a dangerous good

#### International Regulations

##### IATA-DGR

UN/ID No.

: UN 3082

Proper shipping name

: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Tellus S4 VX 32

Version 2.1      Revision Date: 03/04/2021      SDS Number: 800010030788      Print Date: 03/05/2021  
Date of last issue: 08/31/2018

(Distillates (petroleum), hydrotreated middle)  
Class : 9  
Packing group : III  
Labels : 9

### IMDG-Code

UN number : UN 3082  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Distillates (petroleum), hydrotreated middle)  
Class : 9  
Packing group : III  
Labels : 9  
Marine pollutant : yes

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

### Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

## SECTION 15. REGULATORY INFORMATION

### EPCRA - Emergency Planning and Community Right-to-Know Act

#### CERCLA Reportable Quantity

| Components                   | CAS-No.          | Component RQ (lbs) | Calculated product RQ (lbs) |
|------------------------------|------------------|--------------------|-----------------------------|
| <b>Xylene, mixed isomers</b> | <b>1330-20-7</b> | <b>100</b>         | <b>100 (F003)</b>           |
| <b>methyl methacrylate</b>   | <b>80-62-6</b>   | <b>1000</b>        | *                           |

\*: Calculated RQ exceeds reasonably attainable upper limit., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA., The components with RQs are given for information.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Acute toxicity (any route of exposure)  
Skin corrosion or irritation  
Reproductive toxicity

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Tellus S4 VX 32

Version  
2.1

Revision Date:  
03/04/2021

SDS Number:  
800010030788

Print Date: 03/05/2021  
Date of last issue: 08/31/2018

### Clean Water Act

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

|                       |           |          |
|-----------------------|-----------|----------|
| Naphthalene           | 91-20-3   | 0.0001 % |
| Xylene, mixed isomers | 1330-20-7 | 0.0001 % |
| methyl methacrylate   | 80-62-6   | 0.0884 % |

### US State Regulations

#### Pennsylvania Right To Know

|  |            |
|--|------------|
| Distillates (petroleum), hydrotreated middle | 64742-46-7 |
| methyl methacrylate                          | 80-62-6    |

#### California Prop. 65

WARNING: This product can expose you to chemicals including Cumene, Naphthalene, which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

#### California List of Hazardous Substances

|  |            |
|--|------------|
| Distillates (petroleum), hydrotreated middle | 64742-46-7 |
|--|------------|

#### Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The Environmental Protection Agency prohibits processing and distribution of this chemical/product for any use other than in aviation hydraulic fluid in aircraft, lubricants and greases, and new or replacement parts for automobiles and other motor vehicles. In addition, all persons are prohibited from releasing PIP (3:1) to water during manufacturing, processing, distribution in commerce, and commercial use of PIP (3:1).

#### The components of this product are reported in the following inventories:

|       |                          |
|-------|--------------------------|
| REACH | : Not established.       |
| TSCA  | : All components listed. |
| DSL   | : All components listed. |

## SECTION 16. OTHER INFORMATION

### Further information

NFPA Rating (Health, Fire, Reactivity) 1, 1, 0

### Full text of other abbreviations

|                            |  |
|----------------------------|--|
| ACGIH                      | : USA. ACGIH Threshold Limit Values (TLV)  |
| OSHA Z-1                   | : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| ACGIH / TWA                | : 8-hour, time-weighted average  |
| OSHA Z-1 / TWA             | : 8-hour time weighted average   |
| Abbreviations and Acronyms | : The quoted data are from, but not limited to, one or more                        |



# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## Shell Tellus S4 VX 32

Version  
2.1

Revision Date:  
03/04/2021

SDS Number:  
800010030788

Print Date: 03/05/2021  
Date of last issue: 08/31/2018

sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc).

The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial Hygienists

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances

ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council

CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut für Normung

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission

EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and Toxicology Of Chemicals

ECHA = European Chemicals Agency

EINECS = The European Inventory of Existing Commercial Chemical Substances

EL50 = Effective Loading fifty

ENCS = Japanese Existing and New Chemical Substances Inventory

EWC = European Waste Code

GHS = Globally Harmonised System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IC50 = Inhibitory Concentration fifty

IL50 = Inhibitory Level fifty

IMDG = International Maritime Dangerous Goods

INV = Chinese Chemicals Inventory

IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables

KECI = Korea Existing Chemicals Inventory

LC50 = Lethal Concentration fifty

LD50 = Lethal Dose fifty per cent.

LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading

LL50 = Lethal Loading fifty

MARPOL = International Convention for the Prevention of Pollution From Ships

NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level

OE\_HPVS = Occupational Exposure - High Production Volume

PBT = Persistent, Bioaccumulative and Toxic

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## Shell Tellus S4 VX 32

Version  
2.1

Revision Date:  
03/04/2021

SDS Number:  
800010030788

Print Date: 03/05/2021  
Date of last issue: 08/31/2018

---

PICCS = Philippine Inventory of Chemicals and Chemical  
Substances  
PNEC = Predicted No Effect Concentration  
REACH = Registration Evaluation And Authorisation Of  
Chemicals  
RID = Regulations Relating to International Carriage of Dan-  
gerous Goods by Rail  
SKIN\_DES = Skin Designation  
STEL = Short term exposure limit  
TRA = Targeted Risk Assessment  
TSCA = US Toxic Substances Control Act  
TWA = Time-Weighted Average  
vPvB = very Persistent and very Bioaccumulative

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Revision Date : 03/04/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN